BASSPRO TUBE SUBWOOFER

8" (200mm), 10" (254mm) & 12" (300mm) Car Audio Powered Tube Subwoofer System



12" (300mm) Subwoofer



8" (200mm) Subwoofer

Powerful JBL Bass Reinforcement

JBL BassPro Tube Subwoofer delivers 150 Watts of powered noisefree deep bass thanks to JBL's patented Slipstream port technology. The Slipstream port is mathematically engineered to keep airflow with the port turbulence-free, which avoiding the common shortcoming of traditional ported boxes. Coupled with the built-in 150Wrms amplifier the BassPro Tube Subwoofer really delivers. Also the Bass Volume Remote control is included for easy adjustment, no more stopping to pop the trunk.

Features

- Slipstream Port Technology
- Reliable Performance
- Single Tube enclosure Total D Solution
- Bass Volume Remote Control
- Bass boost Volume Control

BASSPRO TUBE SUBWOOFER

8" (200mm), 10" (254mm) & 12" (300mm) Car Audio Powered Tube Subwoofer System



Features and Benefits

Slipstream Port Technology

The Slipstream port technology eliminates turbulence which eliminates noise, inarticulate bass when driven.

Reliable Performance

To ensure that the BassPro Tube Subwoofer stands the test of time, we utilize the rigorous quality control and testing standards. Lifecycle testing pushes each product to its limits, with 215 hours in an environmental testing chamber. Here we freeze them, bake them and give every product a sunburn with 192 hours of ultraviolet light. Speaker products are also subjected to 100 hours of rated power using specific frequencies and music.

Single Tube enclosure Total Solution

The whole system is carefully designed to integrate the 150Wrms amplifier, subwoofer, slipstream port into one tube enclosure, which provides the easiest way to add powerful JBL bass to any car system.

Bass Volume Remote Control

Bass Volume Remote control is included to let you adjust the sound from the driver's seat -no more stopping to pop the trunk.

Bass boost Volume Control

Bass boost Volume control is intergraded on I/O panel to let you adjust the sound freely

What's in the box

- 8" (200mm) Subwoofer
- 1x Powered subwoofer
- 1x Bass volume remote control 2x high level input wiring harness
- 1x 20A fuse

10" (254mm) Subwoofer

- 1x Powered subwoofer 1x Bass volume remote control
- 2x high level input wiring harness 1x 20A fuse

12" (300mm) Subwoofer

1x Powered subwoofer 1x Bass volume remote control 2x high level input wiring harness 1x 20A fuse

Technical Specifications

- 8" (200mm) Subwoofer
 Driver Complement: 8" (200mm) Subwoofer
 Amplifier Power: Class D, 150Wrms,
- 450W peak Frequency Response: 30Hz 200Hz

- Maximum Current Draw: 20 A Quiescent Current Draw: <0.9A Input Sensitivity: 0.15 V 5V Low-Level Input; 0.75 V 25V High-Level Input Crossover Point: 105Hz LPF Crossover Slope: 12 dB/octave Bass Boost: 0dB to + 12dB @ 45 Hz Dimensions (W x H x D): 336(W.H) × 465(D) mm Weight: 15.88 lb (7.2kg)

10" (254mm) Subwoofer

- Driver Complement: 10" (254mm) Subwoofer Amplifier Power: Class D, 150Wrms, 450W peak
- Frequency Response: 30Hz 200Hz Fuse: 20A

- Quiescent Current Draw: <0.9A Input Sensitivity: 0.15 V 5V Low-Level Input; 0.75 V – 25V High-Level Input Crossover Point: 105Hz LPF

- Crossover Slope: 12 dB/octave Bass Boost: 0dB to + 12dB @ 45 Hz Dimensions (W x H x D): 336(W.H) \times 525(D) mm
- Weight: <u>17.64 lb (8kg)</u>

- 12" (300mm) Subwoofer
 Driver Complement: 12" (300mm) Subwoofer
 Amplifier Power: Class D, 150Wrms,
 - 450W max peak Frequency Response: 30Hz 200Hz

- Input Sensitivity: 0.15 V 5V Low-Level Input; 0.75 V 25V High-Level Input

- Crossover Slope: 12 dB/octave Bass Boost: 0dB to + 12dB @ 45 Hz Dimensions (W x H x D): 336(W.H) × 665(D) mm Weight: 19.84 lb (9kg)



HARMAN International Industries, Incorporated 8500 Balboa Boulevard, Northridge, CA 91329 USA © 2023 HARMAN International Industries, Incorporated. All rights reserved. JBL is a trademark of HARMAN International Industries, Incorporated, registered in the United States and/or other countries. Features, specifications and appearance are subject to change without notice